



# ENDOT INDUSTRIES, INC.

PIPE AND TUBING • DUCT AND INNERDUCT

**To Whom It May Concern:**

Endot Industries, Inc. Certifies that the product listed below meets all the Applicable ASTM standards and conforms to NSF Standard 14 for Potable Water.

## EndoPure SPECIFICATION SHEET

**200 PSI - PE 3408**

**APPLICABLE STANDARDS:**

**APPLICABLE STANDARDS:**

NSF	Listed Under Standard 14 for Potable Water
ASTM D3350	Cell Classification - UV Stabilized Clear Center 445576D - UV Stabilized Blue Exterior 445576E
ASTM D2737	Conforms to PE 3408/4710, 200 PSI, SODR 9 (CTS)
ASTM D3035	Conforms as 200 PSI, DR 7 (IPS)
AWWA C901	Conforms as 200 PSI, SIDR 7 (IPS) & SODR 9 (CTS)
BOCA	Conforms as 200 PSI, SIDR 7 (IPS) & SODR 9 (CTS)
Product Requirements:	Color - Exterior Blue with natural core – UV Stabilized with a minimum 5 year Florida sun life Continuous Footage marks every two feet. Permanent Indent printing with Black. Lifetime No Pro-rata Warranty

**WATER SERVICE TUBING (CTS) - ASTM D2737**  
**STANDARD OUTSIDE DIAMETER RATIO (SODR) = 9**

<b>NOMINAL SIZE</b>	<b>NOMINAL O.D.</b>	<b>MINIMUM I.D.</b>	<b>WALL</b>	<b>WEIGHT PER 100 FT.</b>	<b>STANDARD COIL SIZE</b>
3/4	0.875	0.675	.097	10.3	500/100
1	1.125	0.865	.125	17.1	300/100
1-1/4	1.375	1.059	.153	25.5	300/100
1-1/2	1.625	1.253	.181	35.3	300/100
2	2.125	1.629	.236	61.0	200/100

For Endot Industries, Inc. \_\_\_\_\_

Richard G. Kraft, V.P. Sales & Marketing