



ENDOT INDUSTRIES, INC.

PIPE AND TUBING • DUCT AND INNERDUCT

EndoPure SPECIFICATION SHEET

200 PSI - PE 3408/4710

APPLICABLE STANDARDS:

NSF	Listed Under Standard 14 for Potable Water	
ASTM D3350	Cell Classification - UV Stabilized Clear Center	445576D
	- UV Stabilized Blue Exterior	445576E
ASTM D2737	Conforms to PE 3408/4710, 200 PSI, SODR 9 (CTS)	
ASTM D3035	Conforms as 200 PSI, DR 7 (IPS)	
AWWA C901	Conforms as 200 PSI, SIDR 7 (IPS) & SODR 9 (CTS)	
BOCA	Conforms as 200 PSI, SIDR 7 (IPS) & SODR 9 (CTS)	
Product Requirements:	Color - Exterior Blue with natural core –	
	UV Stabilized with a minimum 5 year Florida sun life	
	Continuous Footage marks every two feet.	
	Permanent Indent printing with Black.	
	Lifetime No Pro-rata Warranty	

WATER SERVICE PIPE (IPS) - ASTM D2239
STANDARD INSIDE DIAMETER RATIO (SIDR) = 7

<u>SIZE</u>	<u>NOMINAL O.D.</u>	<u>NOMINAL I.D.</u>	<u>MINIMUM WALL</u>	<u>WEIGHT PER 100 FT.</u>	<u>STANDARD COIL SIZE</u>
3/4	1.070	.824	.118	15.5	400/100
1	1.359	1.049	.150	24.9	300/200/100
1-1/4	1.785	1.380	.197	42.8	300/100
1-1/2	2.086	1.610	.230	58.4	250/100
2	2.675	2.067	.295	96.2	200/100

ENDOT INDUSTRIES, INC.

www.endot.com - e-mail info@endot.com

CORPORATE HEADQUARTERS: 60 Green Pond Road, Rockaway, NJ 07866 – 800 443 6368 – FAX 973 625 4087

MID-WEST OPERATIONS: 739 County Road 1, South Point, OH 45680 – 800 345 3990 – FAX 740 377 9844

TENNESSEE OPERATIONS: 400 Bohannon Avenue, Greeneville, TN 37745 – 800 438 5851 – FAX 423 639 3722

OKLAHOMA OPERATIONS: Mid America Industrial Park, Pryor Creek, OK 74361 – 800 443 6368 – FAX 973 625 4087