

PRODUCTS PIPE A N DTUBING

> SUGGESTED LIST PRICES MARCH 1, 1995

PE 3406 HIGH DENSITY POLYETHYLENE WATER SERVICE LINE

POLY WRAPPED COILS

"PE 3406" - 160 PSI - @73.4°F

(CTS)

WATER SERVICE TUBING

SODR 9

"PE 3406" WATER SERVICE TUBING MAY BE JOINED WITH APPROVED COMPRESSION FITTINGS — DO NOT USE INSERT FITTINGS.

Meets the Requirements of ASTM D2737

SIZE	O.D.	I.D.	Min. Wall	Weight Per 100'	Standard Coil Size	Price Per 100'
3/4 "	875	675	097	10 0	500/100	45 00
1″	1 125	865	125	16.5	300/100	74 50
11/4"	1.375	1.059	.153	24.8	300/100	112.00
11/2"	1 625	1.253	181	34 3	300/100	160 00
2"	2.125	1 629	236	59 2	200/100	277.00

"PE 3406" - 160 PSI - @73.4°F

(IPS)

WATER SERVICE PIPE

SIDR 7

"PE 3406" WATER SERVICE LINE PIPE (IPS) MAY BE JOINED WITH INSERT FITTINGS OR APPROVED IPS COMPRESSION FITTINGS. Compression fittings for IPS PIPE must be selected according to SIDR RATING NOT PRESSURE RATING.

Meets the Requirements of ASTM D2239

SIZE	O.D.	I.D.	Min. Wall	Weight Per 100'	Standard Coil Size	Price Per 100'
3/4 "	1 070	.824	118	15 0	400/100	67.70
1"	1 359	1.049	150	24 1	300/200/100	108.65
11/4"	1.785	1.380	197	41 5	300/100	187.70
11/2"	2 086	1.610	.230	56.6	250/100	269.25
2"	2.675	2.067	.295	93.3	200/100	446.00

STANDARDS:

"PE 3406" pipe meets all the applicable standards of ASTM D1248, ASTM D2737 or D2239, NSF-14, AWWA C901 and BOCA.

GUARANTEE:

ENDOT pipe and tubing is guaranteed against rot, rust and electrolytic corrosion and to be free of defects in material and workmanship. liability will be limited to the replacement of pipe or tubing acknowledged to be defective. (See Warranty for details) Use of pipe sealing compounds, pipe dope and detergent type lubricants voids all warranties.

ENDOT INDUSTRIES, INC.

www.endot.com • e-mail: info@endot.com



