

ENDOT

TECHNICAL SPECIFICATIONS

INDUSTRIES

DUCT AND INNERDUCT

Enduct SMOOTHWALL DUCT AND INNERDUCT

ASTM D 2239 I.D. CONTROLLED

<u>PART NO.*</u>	<u>SDR</u>	<u>SIZE</u>	<u>Nominal O.D.</u>	<u>I.D.</u>	<u>MINIMAL WALL</u>
082/9	9	3/4" (19mm)	1.008" (25.6mm)	0.824" (20.9mm)	0.092" (2.3mm)
082/11.5	11.5	3/4" (19mm)	0.968" (24.6mm)	0.824" (20.9mm)	0.072" (1.8mm)
082/15	15	3/4" (19mm)	0.944" (23.9mm)	0.824" (20.9mm)	0.060" (1.5mm)
105/7	7	1" (25mm)	1.349" (34.3mm)	1.049" (26.6mm)	0.150" (3.8mm)
105/9	9	1" (25mm)	1.283" (32.6mm)	1.049" (26.6mm)	0.117" (3.0mm)
105/11.5	11.5	1" (25mm)	1.231" (31.3mm)	1.049" (26.6mm)	0.091" (2.3mm)
105/15	15	1" (25mm)	1.189" (30.2mm)	1.049" (26.6mm)	0.070" (1.8mm)
125/9	9	1 1/4" (32mm)	1.550" (39.4mm)	1.25" (31.8mm)	0.150" (3.8mm)
125/11.5	11.5	1 1/4" (32mm)	1.470" (37.3mm)	1.25" (31.8mm)	0.110" (2.8mm)
125/15	15	1 1/4" (32mm)	1.410" (35.8mm)	1.25" (31.8mm)	0.080" (2.0mm)
138/7	7	1 1/4" (32mm)	1.774" (45.1mm)	1.380" (35.1mm)	0.197" (5.0mm)
138/9	9	1 1/4" (32mm)	1.686" (42.8mm)	1.380" (35.1mm)	0.153" (3.9mm)
138/11.5	11.5	1 1/4" (32mm)	1.620" (41.1mm)	1.380" (35.1mm)	0.120" (3.0mm)
138/15	15	1 1/4" (32mm)	1.564" (39.7mm)	1.380" (35.1mm)	0.092" (2.3mm)
161/9	9	1 1/2" (38mm)	1.968" (50.0mm)	1.610" (40.9mm)	0.179" (4.5mm)
161/11.5	11.5	1 1/2" (38mm)	1.890" (48.0mm)	1.610" (40.9mm)	0.140" (3.6mm)
161/15	15	1 1/2" (38mm)	1.824" (46.3mm)	1.610" (40.9mm)	0.107" (2.7mm)
206/9	9	2" (51mm)	2.527" (64.2mm)	2.067" (52.5mm)	0.230" (5.8mm)
206/11.5	11.5	2" (51mm)	2.427" (61.6mm)	2.067" (52.5mm)	0.180" (4.6mm)
206/15	15	2" (51mm)	2.343" (59.5mm)	2.067" (52.5mm)	0.138" (3.5mm)

*Any smoothwall product can be ordered with internal ribbing. Simply add the suffix "R" to the part number.

Internal ribs are designed to reduce the surface area of the innerduct for lower friction when installing cable in the innerduct.

For product quantity per reel refer to Endot's reel capacity charts.



Endot Industries, Inc., 60 Green Pond Road, Rockaway, NJ 07866
<http://www.endot.com>
(800) 443-6368 FAX (973) 625-4087