



ENDOT INDUSTRIES, INC.

PIPE AND TUBING • DUCT AND INNERDUCT

Water Flow Characteristics*

Water Service Tubing – ASTM D2737 CTS

Flow Gals. Per Min.	3/4"	1"	1-1/4"	1-1/2"	2"
5	6.6	1.9	-	-	-
10	20.3	7.2	2.3	1.0	0.3
15	42.8	14.3	5.0	2.2	0.6
20	73.4	22.5	8.5	3.7	1.0
25	111.8	32.7	12.8	5.6	1.5
30	-	45.0	17.9	7.9	2.6
40	-	-	30.5	13.5	3.6
50	-	-	-	20.3	5.6
60	-	-	-	-	8.4

* Pressure Loss: psi/100 feet

ENDOT INDUSTRIES, INC.

www.endot.com - e-mail info@endot.com

CORPORATE HEADQUARTERS: 60 Green Pond Road, Rockaway, NJ 07866 – 800 443 6368 – FAX 973 625 4087

MID-WEST OPERATIONS: 739 County Road 1, South Point, OH 45680 – 800 345 3990 – FAX 740 377 9844

TENNESSEE OPERATIONS: 400 Bohannon Avenue, Greeneville, TN 37745 – 800 438 5851 – FAX 423 639 3722

OKLAHOMA OPERATIONS: Mid America Industrial Park, Pryor Creek, OK 74361 – 800 443 6368 – FAX 973 625 4087

