

EndoPoly PE 4710 Copper Tube Size

High Density Polyethylene

- **Meets the Requirements of ASTM D2737**
- EndoPoly water service tubing may be joined with approved compression fittings — DO NOT USE INSERT FITTINGS.

EndoPoly Water Service Tubing | 250 PSI | @73.4°F (CTS) | SODR 9

Size	O.D.	I.D.	Min. Wall	Weight Per 100'
3/4"	0.875"	0.675"	.097"	10.0 lbs.
1"	1.125"	0.865"	.125"	16.5 lbs.
1-1/4"	1.375"	1.059"	.153"	24.8 lbs.
1-1/2"	1.625"	1.253"	.181"	34.3 lbs.
2"	2.125"	1.629"	.236"	59.2 lbs.

Color Specifications

Available in: **Black** (water). EndoPoly pipe & tubing is color-coded with permanent indented printing and footage tape: **Light Blue** Tape = 250 PSI Tubing

Standards

ENDOT's EndoPoly pipe and tubing meets the applicable standards of ASTM D3350 (Cell Classification 445574C), ASTM D2737 or D2239, NSF-14 & 61, AWWA C901, and BOCA

Guarantee

ENDOT's pipe and tubing is guaranteed against rot, rust and electrolytic corrosion, and to be free of defects in material and workmanship. ENDOT's liability will be limited to the replacement of pipe or tubing acknowledged to be defective. See Warranty for details. Use of pipe sealing compounds, pipe dope and detergent type lubricants voids all warranties.

- Chlorine Resistance CC3 & CC2

For the latest information on products and services, visit: endot.com



ENDOT INDUSTRIES

CORPORATE HEADQUARTERS

60 Green Pond Road, Rockaway, NJ 07866
800-443-6368 | FAX 973-625-4087

PLANT LOCATIONS: Rockaway, NJ | Greeneville, TN | Pryor Creek, OK

EMAIL: info@endot.com | endot.com



4/19 1M