

EndoPoly PE 4710 High Density Polyethylene Pipe

High Density Polyethylene Pipe & Tubing

- National Sanitation Foundation (NSF) Certified for use in potable water systems for the transport of drinking water
- · Made from the highest grade PE 4710 bimodal resins available

Sizing Standards

ASTM D2239 Iron Pipe Size (IPS - I.D. Controlled) ASTM D3035 Iron Pipe Size (IPS - O.D. Controlled) ASTM D2737 Copper Tube Size (CTS - O.D. Controlled) ASTM F714 Ductile Iron Pipe Size (DIPS - O.D. Controlled)

Produced in:

- Sizes from 1/2" 12"
- Pressure ratings of 125 PSI, 160 PSI, 200 PSI, 250 PSI, and 333 PSI
- Coils, straight lengths or on reels for continuous lengths

Ideal for:

- · Submersible pump installation in deep wells
- Municipal AWWA C901 & C906 Compliant
- Water service connections & mains
- Sewage force mains & reclaimed water
- Geothermal systems
- Irrigation systems

Exceptionally Durable

EndoPoly is resistant to most chemicals, soil and water conditions without risk of rot, rust, corrosion, or electrolysis.

Made in the USA

EndoPoly is produced and backed by one of the oldest and largest producers of polyethylene tubing in the USA.

Lifetime Warranty - including cost of replacement provisions. See Warranty for details.





ENDOT INDUSTRIES

CORPORATE HEADQUARTERS

60 Green Pond Road, Rockaway, NJ 07866 800-443-6368 | FAX 973-625-4087

PLANT LOCATIONS: Rockaway, NJ | Greeneville, TN | Pryor Creek, OK

EMAIL: info@endot.com | endot.com



4/19 2M