

EndoPoly PE 4710

Iron Pipe Size ID Controlled

High Density Polyethylene

- Meets the Requirements of ASTM D2239

EndoPoly Deep Well & Water Service Pipe | 250 PSI | @73.4°F (IPS) | SIDR 7

| Size | O.D. | I.D. | Min. Wall | Weight Per 100' |
|--------|--------|--------|-----------|-----------------|
| 3/4" | 1.060" | 0.824" | .118" | 15.0 lbs. |
| 1" | 1.349" | 1.049" | .150" | 24.1 lbs. |
| 1-1/4" | 1.774" | 1.380" | .197" | 41.5 lbs. |
| 1-1/2" | 2.070" | 1.610" | .230" | 56.6 lbs. |
| 2" | 2.657" | 2.067" | .295" | 93.3 lbs. |

EndoPoly Deep Well Pipe | 200 PSI | @73.4°F (IPS) | SIDR 9

| Size | O.D. | I.D. | Min. Wall | Weight Per 100' |
|--------|--------|--------|-----------|-----------------|
| 1/2" | 0.760" | 0.622" | .069" | 6.6 lbs. |
| 3/4" | 1.008" | 0.824" | .092" | 11.5 lbs. |
| 1" | 1.283" | 1.049" | .117" | 18.4 lbs. |
| 1-1/4" | 1.686" | 1.380" | .153" | 31.4 lbs. |
| 1-1/2" | 1.968" | 1.610" | .179" | 42.7 lbs. |
| 2" | 2.527" | 2.067" | .230" | 70.7 lbs. |

EndoPoly Water Pipe | 160 PSI | @73.4°F (IPS) | SIDR 11.5

| Size | O.D. | I.D. | Min. Wall | Weight Per 100' |
|--------|--------|--------|-----------|-----------------|
| 1/2" | 0.742" | 0.622" | .060" | 5.7 lbs. |
| 3/4" | 0.968" | 0.824" | .072" | 9.0 lbs. |
| 1" | 1.231" | 1.049" | .091" | 14.2 lbs. |
| 1-1/4" | 1.620" | 1.380" | .120" | 24.3 lbs. |
| 1-1/2" | 1.890" | 1.610" | .140" | 27.1 lbs. |
| 2" | 2.427" | 2.067" | .180" | 53.0 lbs. |

EndoPoly Irrigation & Water Pipe | 125 PSI | @73.4°F (IPS) | SIDR 15

| Size | O.D. | I.D. | Min. Wall | Weight Per 100' |
|--------|--------|--------|-----------|-----------------|
| 3/4" | 0.944" | 0.824" | .060" | 7.5 lbs. |
| 1" | 1.189" | 1.049" | .070" | 10.9 lbs. |
| 1-1/4" | 1.564" | 1.380" | .092" | 18.5 lbs. |
| 1-1/2" | 1.824" | 1.610" | .107" | 24.9 lbs. |
| 2" | 2.343" | 2.067" | .138" | 40.9 lbs. |
| 3" | 3.478" | 3.068" | .205" | 89.1 lbs. |

Tape Color Specifications - Available in: **Black** (water). EndoPoly Pipe is color-coded with permanent printing and footage tape:
Orange Tape = 250 PSI **Yellow** Tape = 200 PSI **Red** Tape = 160 PSI **Green** Tape = 125 PSI

Standards - ENDOT's EndoPoly pipe meets the applicable standards of ASTM D3350 (Cell Classification 445576C and 445574C), ASTM D2239, NSF-14 & 61, and BOCA

Note - Use of pipe sealing compounds, pipe dope and detergent type lubricants voids all warranties. Use insert fittings for all sizes and pressure ratings. COMPRESSION FITTINGS FOR 250 PSI PIPE MUST BE SELECTED ACCORDING TO SIDR RATING AND NOT PRESSURE RATING.

- Chlorine Resistance CC3 & CC2

For the latest information on products and services, visit: endot.com



ENDOT INDUSTRIES

CORPORATE HEADQUARTERS

60 Green Pond Road, Rockaway, NJ 07866
800-443-6368 | FAX 973-625-4087

PLANT LOCATIONS: Rockaway, NJ | Greeneville, TN | Pryor Creek, OK

EMAIL: info@endot.com | endot.com



4/19 1.5M